



## Hamper Door Installation Instructions

- Using a 1/16" drill bit, drill four (4) pilot holes in the backside of the hamper door for the two (2) sliding stay brackets. See illustration below for placement. Pilot holes should not exceed 7/16" depth to avoid coming through the face of the door. For a depth gauge, measure from the bottom of the drill bit up 7/16" and wrap a piece of masking tape around the bit.
- Mount the sliding stay brackets (L bracket end) to the back of the hamper door using two (2) #6 x 1/2" pan head screws.
- (Before installing the hinges, read this entire section to get familiar with how the Euro hinge locks to the mounting plate. This will be helpful when actually placing the door in position.) Insert the hinge cup into the pre-drilled holes on the back side of the hamper door. Tighten the hinge screws in place. Mount the hinge mounting plate to the top of the bottom shelf using the pre-drilled holes in the shelf. Positioning the arrow on the plate at the front of the shelf facing towards the door, install the hinge in the open or extended position, slide the hinge grippers (hooks) under the front of the mounting plate. Push the back of the hinge down until it snaps (locks) into the mounting plate. To remove the hinge from the plate, pull back on the spring clip at the rear of the hinge and lift off.
- From the bottom shelf, count up the vertical panels to front line boring holes 10 & 11. Mount the white plastic end of the stay bracket to the vertical panels, using two (2) 5MM x 1/2" Euro screws.
- Adjust the slide rail tension on the stay bracket by turning the white plastic screw in the center of the white plastic mounting plate.

